

ISO
3376

IULTCS/IUP 6

**Leather — Physical and mechanical
tests — Determination of tensile
strength and percentage elongation**

*Cuir — Essais physiques et mécaniques — Détermination de la
résistance à la traction et du pourcentage d'allongement*





COPYRIGHT PROTECTED DOCUMENT

below or ISO's member body in the country of the requester.

CP 401 • Ch. de Blandonnet 8

Contents

F

1 S

2 N

3 O

4 P

5 M

6 H

7 P

8 E

9 T

Foreword

*L
e
a
t*

Any feedback or questions on this document should be directed to the user's national standards body. A

Leather — Physical and mechanical tests — Determination of tensile strength and percentage elongation

1 Scope

2 Normative references

Leather — Chemical, physical and mechanical and fastness tests — Sampling location

Leather — Physical and mechanical tests — Sample preparation and conditioning

Leather — Physical and mechanical tests — Determination of thickness

Metallic materials — Calibration and verification of static uniaxial testing machines — Part 1: Tension/compression testing machines — Calibration and verification of the force-measuring system

3 Terms and definitions

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia. available at <http://www.electropedia.org/>

4 Principle


5 Apparatus

5.1 T

5.2 A

5.3 T

5.4 P
r



Key

l

b

Figure 1 — Shape of test piece

Table 1 — Dimensions of test pieces

Test piece size	<i>l</i>			<i>b</i>		<i>R</i>
Standard						
L						

5.5 V

6 Sampling and sample preparation

6.1

6.2

6.3

7 Procedure

7.1 Determination of dimensions

7.1.1

7.1.2

-

7.2 Determination of tensile strength

7.2.1

—
—

7.2.2

7.2.3

7.2.4

Variable results can occur if using the force at the test piece's break, F_{break} , instead of F_{max}

7.3 Determination of the percentage elongation caused by a specified load

7.3.1

F

- for $F_{max} \leq 100$ N, a pre-load of 0,5 N;
- for $100 N < F_{max} \leq 300$ N, a pre-load of 2,0 N;

—

If the leather's maximum force, F

7.3.2

7.3.3

7.4 Determination of the percentage elongation at maximum force

7.4.1

7.4.2

7.4.3

Variable results can occur if using the elongation at the test piece's break, E_{break} , instead of E_{max} ,

7.5 Slippage

8 Expression of results

8.1 Tensile strength

$$T_n = \frac{F_w}{t} =$$

\bar{w}

t

8.2 Percentage elongation caused by a specified load

8.3 Percentage elongation at maximum force

$$E_{\max} = \frac{L_2 - L_0}{L_0} \times 100$$

9 Test report

