
Metallic materials — Bend test

Matériaux métalliques — Essai de pliage



COPYRIGHT PROTECTED DOCUMENT

below or ISO's member body in the country of the requester.

CP 401 • Ch. de Blandonnet 8

Contents

F

1 S
2 N
3 O
4 S
5 n
6 n

7 T

8 P

9 F
10 O

A n d

A

B

--

Foreword

M
Đ
ECISS – European Committee for Iron and Steel Standardization,
h

Any feedback or questions on this document should be directed to the user's national standards body. A

Metallic materials — Bend test

1 Scope

2 Normative references

3 Terms and definitions

— IEC Electropedia: available at <http://www.electropedia.org/>

— ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Symbols, designations and units

Table 1 — Symbols, designations and units

Symbol	Designation	Unit
a		
b		
c		
D		
f		
$\bar{\theta}$		—
L		
l		
η		—
p		
R		
r		
α		

5 Principle

-

6 Test equipment

6.1 General





Figure 1 — Bending device with two supports and a former

6.2 Bending device with supports and a former

6.2.1

6.2.2



6.3 Bending device with a V-block

The tapered surfaces of the V-block shall form an angle of $180^\circ - \alpha$ (see [Figure 2](#)). The angle α is specified

6.4 Bending device with a clamp

7 Test piece

7.1 General

7.2 Edges of rectangular test pieces

—

- 1,5 mm, when the thickness of the test pieces is less than 50 mm and more than or equal to 10 mm;
- 1 mm when the thickness is less than 10 mm.

7.3 Width of the test piece

7.4 Thickness of the test piece

7.4.1

7.4.2




Figure 4 — Diameter and inscribed circle diameter of the test piece

7.5 Test pieces from forgings, castings and semi-finished products

7.6 Agreement for test pieces of greater thickness and width

7.7 Length of the test piece

8 Procedure

WARNING — During the test, adequate safety measures and guarding equipment shall be provided.

8.1

8

.




Figure 5 — Bending the legs of the test piece



Figure 6 — Legs of the test piece parallel to each other




Figure 7 — Legs of the test piece in direct contact

8.3

α , can be calculated from the measurement of the displacement of the former as

8.4

9 Interpretation of results

9.1

9.2

10 Test report

Annex A

Determination of the bend angle from the measurement of the displacement of the former

α , of a test piece under force. The direct

α , of the test piece

$$\sin \frac{\alpha}{2} = \frac{p \times c + W \times (f - c)}{p^2 + (f - c)^2}$$

$$\cos \frac{\alpha}{2} = \frac{W \times p - c \times (f - c)}{p^2 + (f - c)^2}$$

$$W = \sqrt{\frac{c^2 + (f - c)^2 \sin^2 \frac{\alpha}{2}}{\cos^2 \frac{\alpha}{2} - \sin^2 \frac{\alpha}{2}}}$$





Figure A.1 — Values for the calculation of the bend angle, α

Annex B

Bend test at plane strain conditions

B.1 Overview



Key

$b \geq 10 \times a$ and $a > 3$ [see [Annex B](#)]

$b \geq 10 \times a$

$a \geq 3$ [see [7.3 b](#) 2)]

$b \leq 20$ [see [7.3 a](#))]

Figure B.1 — Combinations of thickness (a) and width (b) in relation to plane strain condition, for test pieces given in [7.3](#)

b
 $a) \geq 10$ should be employed.

-
- as a consequence, test pieces can fail;
- increase of the testing force;
- increase of the weight of the test piece;
- the bendability requirements in product standards may not be fulfilled.

B.2 General

η
 η , and the
 θ
 θ

$$\cos \frac{\pi(1-\theta)}{2} = -\frac{2}{3} \left(\frac{\eta}{2} - \sqrt{\frac{\eta}{2}} \right)$$




Figure B.2 — Differences in bendability depending on width (b)

B.3 Test piece

$a) \geq 10$ shall be used.

B.4 Assessment

B.5 Test report

Bibliography

- R. "The Mathematical Theory of Plasticity". Clarendon Press, Oxford, (1950)
- , "Plastic sheet bending", Ph.D. Thesis, Chalmers Tekniska Högskola, Göteborg, (1970)
- J. L. "The Mechanics of Sheet Metal Forming," Edward Arnold Ltd., London, (1992)
- Chan W.M., Chew H.P., Lee B.T., "Finite element analysis of spring-back of V-bending sheet metal forming processes", *Int. Journal of Materials Processing Technology*, **148**, 15–24, (2004)
- Cheong K. et al. "Evaluation of the VDA 238-100 Tight Radius Bending Test using Digital Image Correlation Strain Measurement", *Int. Journal of Physics, Conf. Ser.* **896** 012075, (2017)
- Li Y., Wierzbicki T., "Prediction of plane strain fracture of AHSS sheets with post-initiation softening", *Int. Journal of Solids and Structures* **47**, 2316–2327, (2010)
- Bai Y., Wierzbicki T., "A new model of metal plasticity and fracture with pressure and Lode dependence", *Int. Journal of Plasticity* **24**, 1071–1096, (2008)
- Wierzbicki T., Xue L. "On the Effect of the Third Invariant of the Stress Deviator on Ductile Fracture". *Technical Report*, Impact and Crashworthiness Laboratory, Massachusetts Institute of Technology, (2004)
- Bai Y., Wierzbicki T., "Application of extended Mohr-Coulomb criterion on ductile fracture", *Int. Journal of Plasticity* **24**, 1097–1115, (2008)

